



VPL-EW5

WXGA Multi-use projector with 2'000 lumens

☐ --Overview--

Native Resolution	WXGA (1280 x 800 x 3)
Panel Type	BrightEra Inorganic 0.63-inch TFT LCD, 2,359,296 pixels
Projection System	3 LCD panels, 1 lens system
Brightness	1600/2000 ANSI lumen
Contrast Ratio	700:1
Weight	Approx. 3kg
Dimensions	(W x H x D) 314 x 109 x 269 mm

☐ --General--

Standard Lens Zoom	1.2 times (Manual)
Vertical Keystone Correction	+/- 30°
Lamp Type	190W Ultra High Pressure
Lamp Life	(Replacement time) 3000 H
Filter Cleaning Time	3000 H
Speaker	1W Mono
Max Power Consumption	260W
Standby Power Consumption	3W
Body Colour	White

☐ --Throwing Distance--

Min - Max Screen Size (diagonally)	40-300 inch
40-inch / 1m screen	1.1 – 1.4m
80-inch / 2m screen	2.3 – 2.8m
100-inch / 2.5m screen	2.9 – 3.5m
200-inch / 5.1m screen	5.8 – 7.0m
300-inch / 7.6m screen	8.8 - 10.5m

☐ --Signals--

Colour System	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60 system
---------------	--

☐ --Inputs--

Input A	HD D-sub 15-pin (RGB/Component)
Video	S-Video Composite Video
Acceptable video signal	Composite Video, Y/C Video, 15kRGB 50/60Hz, Progressive Component 50/60Hz, DTV (480/60i, 480/60p, 575/50i, 575/50p, 720/50p, 720/60p, 1080/50i, 1080/60i,)
Audio	Stereo Minijack (shared VIDEO IN/INPUT A)

☐ --Control--

RS-232C	D-sub 9-pin
---------	-------------

☐ --Output--

Monitor out	HD D-sub 15-pin (RGB)
Audio out	Stereo Minijack (variable)

☐ --Supplied accessories--

Remote Commander

RM-PJ4 (credit card style)

Carrying Case

Soft Type

Cables

HD D-sub 15 pin (2m)

☐ --Optional accessories--

Lamp

LMP-E190

☐ Supplied Accessories

Warranty card

Security label

Safety regulation booklet

Quick reference manual

Operating Instructions (CD-ROM)

AC Power cord

Soft carrying case

HD D-sub 15 pin cable 1.8m

Lithium battery CR2025

Remote Commander Unit (RM-PJ4)